



268L



328L



270L/350L

Technical Parameters

Model	BDF-25V268	BDF-25V328	BDF-25V270	BDF-25V350
External Size(W*D*H) mm	673*676*1630	673*676*1886	690*744*1631	690*744*1885
Capacity	268L	328L	270L	350L
Type	Vertical			
Temp. Range	-10°C~-25°C		-15°C~-25°C	
Temp. Accuracy	0.1°C			
Control System	Microprocessor Control & LED Display			
Alarm	High and low temperature; System & sensor failure; Door ajar; Power failure alarm; Thermostat alarm		High or low temperature alarm, Sensor failure alarm, power failure alarm, abnormal door opening and closing alarm	
Refrigeration Type	Direct Refrigeration			
Refrigerant	R290, CFC free			
Compressor	International famous compressor			
Condenser & Evaporator	High efficiency air-cooled condenser, made of copper		Bundy tube condenser and inner coil tube evaporator	
Structure	Unibody Design & Mono-assembly foaming (Rigid polyurethane insulation material)			
Construction Internal Material	Cold-rolled steel coated with		SUS304	
External Material	anti-bacteria powder		Cold-rolled steel coated with bacterial powder	
Shelve/Inner Door	4pcs	5pcs	4pcs	5pcs
Consumption	280W	280W	290W	305W
Power Supply	AC220V±10%, 50/60Hz	110V60HZ	220V±10%;50Hz	
Package Size(W*D*H) mm	760*770*1800	770*770*2040	810*860*1820	810*860*2100
Gross Weight	125kg	140kg	155kg	170kg