



EyeCGas® CO

Hand-held Optical Gas Imaging Camera
for Carbon Monoxide

4 NOW WITH A
YEAR
WARRANTY*



EyeCGas® CO is a handheld OGI camera for CO gas leak detection. With this OGI camera you can safely and remotely detect and locate carbon monoxide as well as other harmful gas emissions. Whether these toxic gases are part of the manufacturing process, or a byproduct of the production line, EyeCGas® CO helps increase safety and protect the environment. Discover unparalleled safety and efficiency with the EyeCGas CO camera. Effortlessly and remotely identify and pinpoint carbon monoxide and other hazardous gas emissions. Opgal's EyeCGas CO camera is among the select few certified for ATEX Zone 2 and UL Class I Div

II, ensuring unprecedented performance even in the most challenging hazardous environments. EyeCGas 2.0 CO enables you to Stream your inspection in real time, or share your results using the dedicated EyeCGas App. Receive free software upgrades, which are based on customer feedback, and rest assure that your investment is guaranteed with our exclusive 4-year warranty.



STREAMING

Real-time video streaming and wireless images/videos sharing with the official EyeCGas App.

KEY FEATURES

• Gas Leak Detection

Quick detection of CO and CO2.

• Thermographic Imaging

Temperature measurements capabilities and color pallets for better versatility.

• Connectivity

Built-in Wi-Fi, GPS, hotspot and Bluetooth capabilities.

• Meets Regulatory Compliance

Complies with the EPA's Quad Oa (OOOO'a/b/c) regulations.

• Gas Quantification

Built-in quantification or remotely operated quantification via EyeCSite software and other 3rd party devices.

• LDAR-Ready Capabilities

Integrates with various softwares and analyzers.

• Free Firmware Upgrades

Receive camera upgrades and improvements free of charge.

• Intrinsically Safe

IECEx intrinsically safe Zone II, ANSI, CSA Class I & Class II div.2.

• Rugged & Sealed

Especially designed for detecting gas leaks in the harsh conditions of the oil and gas industry.

• Multi Spectral OGI

Replaceable filters enabling CO2 detection with the same camera.

SPECIFICATIONS

| | |
|---------------------------------|---|
| IR Resolution | 320 x 240 pixels |
| Focus | Manual Focus |
| Detector Pitch | 30 µm |
| Thermal Sensitivity/ NETD | <10 mK at 30°C (86°F) |
| Gas Sensitivity | 5.0 ppm m, ΔT =10°C, 1 m/s wind speed, distance 2m |
| Hazardous Location Compliance | CSA C22.2 No. 213-M1987, Non-Incentive Electrical Equipment for Use in Class I, Division 2, ANSI/ISA-12.12.01 – Class I and II, Division 2, and Class III, ATEX. Intrinsically safe for Zone 2 ratings as: Ex II 3 GD; Ex ic nA nC IIC T6 Gc; Ex ic tc IIIC T85°C DC |
| Gas leak detection capabilities | WITH SPECTRAL filter of 4.0µm to 4.7µm for arbon monoxide and Carbon dioxide |

| Detector and Optical Data | |
|---------------------------|---|
| Detector Type | Focal plane array (FPA), cooled MCT |
| Spectral Range | 4.0 µm to 4.7 µm |
| Replaceable filters | CO2 4.1-4.4 µm |
| Sensor Cooling | Stirling Microcooler |
| Digital Image Enhancement | High sensitivity mode (HSM), noise reduction filter |
| Available Lenses | 18° (30 mm); 7.5° (75 mm) |
| F-Number | 1.1 |

| Image Presentation | |
|--------------------------|--|
| Display | 3.5" (10'equivalent using glare shield), 640 x 480 pixel, LCD |
| Image Presentation Modes | IR image, visual image, Normal, Enhanced & Thermography |
| Color Palettes | 6 color palettes (Rainbow, Iron, ISO red, ISO green, Grey Scale and Vivid) |
| Zoom | x2, x4, x8 and x16 (only for visible camera) |

| Measurement & Analysis | |
|-------------------------------|---|
| Measurement Temperature Range | -20°C to 350°C (-4°F to 662°F) |
| Accuracy | At Least ± 1 °C (0 – 100 °C), ± 2% (> 100 °C), ± 2°C (-20 – 0 °C) |
| Gas emission Quantification | Built-in real-time and offline Image processing gas quantification for desktop or handheld application (offline/online operation) |

| Accessories & Apps | |
|--------------------|--|
| Head up display | Seamless integration including voice commands with Realware® head up display |
| Mobile APP | Android 10 /IOS 14 and up |

| Communication interface & Data Storage | |
|--|--|
| GPS | Included, can be added to any still or video recording |
| Storage Media | Up to 20 hours and more of video storage over a 64-GB solid state memory |
| Image File Formats | JPG Format (on available modes) |
| Communication Interfaces | USB: Data transfer, video streaming and video images file transfer Wi-Fi: 2.4 GHz for video streaming and file transfer Bluetooth: Bluetooth 4.2 with other devices: RMLD, TVA2020 ,LDAR software etc... GPS: Built in or external |
| Video Out | Digital video recorder build-in generates a .ts format video on all modes. |

| Video Recording and Streaming | |
|--------------------------------|---|
| IR or Visual Video | Digital video recorder build-in generates a .ts format video on all |
| Radiometric IR Video Streaming | Over Wifi |

| Environmental & Certifications | |
|--------------------------------|--|
| Operating Temperature Range | -20°C to 50°C (-4°F to 122°F) |
| Storage Temperature Range | -40°C to 70°C (-40°F to 158°F) |
| Encapsulation | IP65 (Intrinsically safe) |
| Drop | ASTM-D 4169-06 Schedule A |
| Vibration | ASTM-D 4169-08 Schedule F Test method D999 |
| HALT | Max temp: 55°C, Min temp: -20°C |
| Safety | EN60950-1:2006 |

| Additional Information | |
|------------------------|--|
| Battery Type | Rechargeable Li-ion battery; 7.4 V, charger included |
| Battery Operating Time | >4.5 hours continuous operation |
| Battery Charging Time | 3 hours to 95% capacity, charging status indicated by LEDs |
| Camera Size | 9" x 4.3" x 5.1" (230 x 110 x 130) mm |
| Camera Weight | 2.6 kg (5.9 lb) |
| Mounting Interfaces | UNC ¼"-20 |
| Warranty | 4 years (Detector & cooler – 2 years; Batteries 1 year) |

| Box Contents | |
|--------------|--|
| Packaging | Infrared camera with lens, Batteries (2), Battery Charger, USB Cable, Neck strap, Glare Shield, Carrying Case, Cleaning Kit. |

